



TCF/F

Filling plug with breather and milled head

- ▶ Hole for venting internal pressure.
- ▶ The milled head produces a crown with greater adherence area to the crankcase.
- ▶ For application only on upper part of the crankcase away from moving parts.
- ▶ For applications requiring extra-tight sealing, type TSFT/N is recommended.


[PRINTING NOTES](#)
[PRINT](#)

TYPE	CODE	GAS	d	t	f	e
TCF/F0G	1GF/F00A	1/8"	14	7	8	10
TCF/F1G	1GF/F10A	1/4"	20	8	8	17
TCF/F2G	1GF/F20A	3/8"	22	10	9	18
TCF/F3G	1GF/F30A	1/2"	28	10,5	11	22
TCF/F4G	1GF/F40A	3/4"	32	10,5	12	27
TCF/F5G	1GF/F50A	1"	40	10,5	12,5	34

TYPE	CODE	MB series	d	t	f	e
TCF/F0M	1MF/F00A	10 x 1	14	7	8	10
TCF/F1M	1MF/F10A	14 x 1,5	20	8	8	17
TCF/F2M	1MF/F20A	16 x 1,5	22	10	9	18
TCF/F3M	1MF/F30A	18 x 1,5	26	8	9	20
TCF/F4M	1MF/F40A	20 x 1,5	28	9	11	22
TCF/F5M	1MF/F50A	22 x 1,5	28	10,5	11	22