



TCSF/Z

Filling plug and breather

- ▶ Threaded plug with knurled round head for hand-tightening.
- ▶ The hole and a spherical bronze filter vent internal pressure and keep out foreign bodies during the intake stroke.
- ▶ The built-in filter has a filtration degree of 40 microns.
- ▶ The TCSF/Z is therefore especially suitable in dusty environments and is recommended for applications on **Hydraulic Units**.


[PRINTING NOTES](#)
[PRINT](#)

TYPE	CODE	GAS	h	f	d	μ
TCSF/Z1G	1GSFZ10A	1/4"	12	8	22	40
TCSF/Z2G	1GSFZ20A	3/8"	12	10	26	40
TCSF/Z3G	1GSFZ30A	1/2"	15	12	30	40
TCSF/Z4G	1GSFZ40A	3/4"	20	13,5	40	40
TCSF/Z5G	1GSFZ50A	1"	20	14	45	40
TCSF/Z6G	1GSFZ60A	1" 1/4	20	16	55	200
TCSF/Z7G	1GSFZ70A	1" 1/2	20	16	55	200
TCSF/Z8G	1GSFZ80A	2"	20	17	70	200

TYPE	CODE	MB series	h	f	d	μ
TCSF/Z1M	1MSFZ10A	14 x 1,5	12	8	22	40
TCSF/Z2M	1MSFZ20A	16 x 1,5	12	10	26	40
TCSF/Z3M	1MSFZ30A	18 x 1,5	12	10	26	40
TCSF/Z4M	1MSFZ40A	20 x 1,5	15	12	30	40
TCSF/Z5M	1MSFZ50A	22 x 1,5	15	12	30	40
TCSF/Z6M	1MSFZ60A	24 x 2	15	13,5	36	40
TCSF/Z7M	1MSFZ70A	30 x 2	20	14	42	40
TCSF/Z8M	1MSFZ80A	33 x 2	20	14	45	40