



TSFA

Oil filling plug and breather

- ▶ A galvanized-steel cover and a spherical bronze filter vent internal pressure and keep out foreign bodies during the intake stroke.
- ▶ The built-in filter has a filtration degree of 40 microns.
- ▶ The TSFA is therefore especially suitable in dusty environments and is recommended for applications in the **motor field**.


[PRINTING NOTES](#)
[PRINT](#)

The articles marked * are extra-table.

TYPE	CODE	GAS	d	h	f	e	μ
TSFA0G	1GTSFA0M	1/8"	16,5	16	8	14	40
TSFA1G	1GTSFA1M	1/4"	16,5	17	8	17	40
TSFA2G	1GTSFA2M	3/8"	22	19	11	22	40
TSFA3G	1GTSFA3M	1/2"	26	20	11	27	40
TSFA4G	1GTSFA4M	3/4"	30	24	12	32	40
TSFA5G	1GTSFA5M	1"	38	29	14	40	40

TYPE	CODE	MB series	d	h	f	e	μ
TSFA0M	1MTSFA0M	10 x 1	16,5	16	8	14	40
TSFA1M	1MTSFA1M	12 x 1,5	16,5	17	8	17	40
TSFA2M	1MTSFA2M	14 x 1,5	16,5	17	8	17	40
TSFA3M	1MTSFA3M	16 x 1,5	22	19	11	22	40
TSFA4M	1MTSFA4M	18 x 1,5	22	19	11	22	40
TSFA5M	1MTSFA5M	20 x 1,5	24	20	11	24	40
TSFA6M	1MTSFA6M	22 x 1,5	26	20	11	27	40
TSFA7M	1MTSFA7M	24 x 1,5 *	30	24	12	30	40
TSFA8M	1MTSFA8M	26 x 1,5 *	30	24	12	32	40
TSFA9M	1MTSFA9M	30 x 1,5 *	30	25	14	36	40