



# TSVV

## Breather plug with double valve

- ▶ Breather plug with double valve made of hardened and tempered light alloy. It is provided with standard 0,10 bar calibration, which can be adjusted by the operator depending on the intended use.
- ▶ The double valve ensures venting of internal pressure and inlet of air when the flow medium level decreases thus hindering cavitation on delivery.
- ▶ Particularly suitable for **Tanks, Oil-hydraulic Circuits and Hydraulically Operated Lifting Machines.**


[PRINTING NOTES](#)
[PRINT](#)

The articles marked \* are extra-table.

TYPE	CODE	GAS	t	f	e
TSVV1G	1GSVV10A	1/4"	10	10	17
TSVV2G	1GSVV20A	3/8"	10	10	22
TSVV3G	1GSVV30A	1/2"	10	10	27
TSVV4G	1GSVV40A	3/4"	8	12	32
TSVV5G	1GSVV50A	1"	8	14	40

TYPE	CODE	MB series	t	f	e
TSVV0M	1MSVV00A	12 x 1,5	16	10	17
TSVV1M	1MSVV10A	14 x 1,5	10	10	17
TSVV2M	1MSVV20A	16 x 1,5	10	10	22
TSVV3M	1MSVV30A	18 x 1,5	10	10	22
TSVV4M	1MSVV40A	20 x 1,5	10	10	24
TSVV5M	1MSVV50A	22 x 1,5	10	10	27
TSVV6M	1MSVV60A	24 x 1,5	10	10	30
TSVV7M	1MSVV70A	26 x 1,5	8	12	32
TSVV8M	1MSVV80A	30 x 2	8	12	36
TSVV9M	1MSVV90A	33 x 2	8	14	40